



HRC-P6502C

24

360

100m—2000m

IP67

150

1.

24

2.

3.

135

4.

5.

6.

7.

IP67

8.

9. IP

10.

11. +

12.

13. GIS

14.

15.

| | | |
|--|---|---|
| | | |
| | | HRC-P6502C |
| | | 1/3" 1/2.8 1/2" 1/1.8" 1/1.7" CMOS/CCD |
| | | 130 /200 /300 /500 /600 /4K |
| | | 30x /36x /38x /40x |
| | | 4.3-129mm/6-180mm/6-216mm/8.1-310mm/10-400mm |
| | | ICR |
| | | :0.002 Lux :0.0002Lux |
| | | / / |
| | / | / / / |
| | | H.265/H.264/MJPEG |
| | | TCP/IP UDP IGMP ICMP DHCP HTTP HTTPS DHCP DNS DDNS RTP/RTSP PPPoE SMTP UPnP NTP ARP ONVIF/PSIA |
| | | |
| | | 8~14um |
| | | |
| | | 640x480/17μm 640x480/17μm |
| | | 25mm/50mm 33/50mm 33/50mm 25~50mm 33~50mm |

| | | |
|--|----|---|
| | | |
| | | HRC-P6502C |
| | | 13 |
| | | |
| | | |
| | | 0.01° 45°/S 0.1° 30°/S |
| | | 0 360° +60° -60° |
| | | 256 |
| | | ±0.01° |
| | | Pelco-D Pelco-P |
| | | 2400/4800/9600/19200 bps |
| | | RS485 |
| | | |
| | IP | |
| | | |
| | | |
| | | 32 |
| | | 4 10 |
| | | DC24V/AC24V 50Hz |
| | | -45 70 |
| | | |
| | | 15Kg |
| | | 80W |
| | | IP67 |
| | | 510mm × 350mm × 300mm L×W×H |



C 13

0755-86518800 0755-86518855
QQ 76024879
sales@ huaruicom.com
www.huaruicom.com



15333833961
13632702325

13632702323
0551-65837321

15104440003
029-82098966

15889666061
028-86658015

027-87879966
0871-68358002

021-63550300
15978139595