



HRC-P6200Z100L25 云 , 专为 , 主

A , 万 ,  
 3-5 km , 10-15km , 于  
 IP66 , , 150 下  
 , 以

1. 产 , 不
2. : , 以
3. 云 : 云 ,
4. , , ,
5. IR : 不 , 人
6. : , 中 , 以
7. 与 , 人
7. FTIS ATPC , 了
8. 256个 ( 0.01° ) , 8 ,

		HRC-P6200Z100L25
		200万 1/1.8" CMOS
		1920 × 1080 , ≥1100TVL
		:0.001 Lux @(F1.2,AGC ON) :0.0001Lux @(F1.2,AGC ON)
		/ ,ICR ,
		20-1000mm , 二 40-2000mm , ( )
		0.38-17.8°
		100X
		( )
		ABF
		H.264/MPEG4/MJPEG
		: 1920×1080@60fps , 1280×960@60fps , 1280×720@60fps , 为 H.265 H.264 MPEG-4 MJPEG ; H.264 H.265 为 Baseline/Main/High Profile
		32Kbps~16Mbps , 丢 为 20% 下 , 仍
		1-25f/s(50Hz), 1-30f/s (60Hz)
		810nm , 808nm/915nm/950/975nm
		4000
		0.2°~20° ,
		25W
		/
		0.01
云		
		50kg
		360° , -45°~45° ( , -80°~80° )
		0.01°/ 30°/ ; 0.01°/ 20°/
		256个 ,



		HRC-P6200Z100L25
		云
		RS-422/RS-485
		PELCO-D/P
		1 个 RJ45 10M / 100M/1000M 以
		16 , 10 以上
		DC24V
		-45°C ~ 70°C
	他	
		8000V
		35Kg
		≤100W , ≤150W
		IP67
		657(L)x378(W)x610(H)

; ; ; 事 ; ; ;  
 ; ; ; ; ; ; ;  
 ; ; ; 事 ; 事 ; ; ;  
 ; ; ; 仓 ; ; ; ;  
 ; ; 中

